



Performance Data  
eVP-10 with eVector technology

**eVP-10** (170Kv)

Mass of EV-10 is ~300 grams

ESC	Voltage	Prop	Prop	Current (A)	Power (W)	Thrust (lbs)	Thrust (g)	Grams/Watt	Operation Temperature (C)
HV-Pro 14s	48	21"x7	21"x7	4	192	4	1814	9.45	>80 C
				5.1	244.8	4.5	2045	8.35	
				6.2	297.6	5.2	2364	7.94	
				8.1	388.8	6.4	2909	7.48	
				9.1	436.8	7.1	3227	7.39	
				10.4	499.2	7.8	3545	7.10	
				11.2	537.6	8.2	3727	6.93	
		12.2	585.6	8.7	3955	6.75			
		21.5"x8.1	21.5"x8.1	4.2	201.6	4	1818	9.02	>90 C
				5	240	4.7	2136	8.90	
				6.8	326.4	6	2727	8.35	
				8.3	398.4	6.8	3091	7.76	
				10	480	7.9	3583	7.46	
		23"x7.4	23"x7.4	4	192	4	1818	9.47	>90 C
				4.8	230.4	4.6	2091	9.08	
				5.8	278.4	5.4	2455	8.82	
				7.1	340.8	6.2	2818	8.27	
				8	384	6.7	3045	7.93	
				9	432	7.5	3409	7.89	
				10.5	504	8.3	3773	7.49	
				11.1	532.8	8.6	3909	7.34	
		12	576	9	4091	7.10			
		14	672	10.3	4682	6.97			
		24.5"x8.1	24.5"x8.1	4.2	201.6	4.4	2000	9.92	>110 C
				5.1	244.8	5.1	2318	9.47	
				6.3	302.4	6	2727	9.02	
				8.2	393.6	7.1	3227	8.20	
				10.3	494.4	8.3	3773	7.63	
				12.6	604.8	9.6	4364	7.22	
		14.1	676.8	10.6	4818	7.12	<110 C After 10 min		
		27.5"x8.9	27.5"x8.9	4	192	5	2273	11.84	>110 C
				6	288	6.4	2909	10.10	
8	384			8	3636	9.47			
10	480			9	4091	8.52			
12	576			10	4545	7.89			
14	672			10.6	4818	7.17			
16	768			12	5455	7.10			
18	864			12.9	5851	6.77			
20	960	13.5	6123	6.38	<110 C After 10 min				



Performance Data  
eVP-10 with eVector technology

**eVP-10 (240Kv)**

ESC	Voltage	Prop	Prop	Current (A)	Power (W)	Thrust (lbs)	Thrust (lbs/g)	Grams/Watts	Operation Temperature (C)	
HV-Pro 14s	24	18.5"x6.3	18.5"x6.3	4	192	2.1	955	4.97	>70	
				5	240	2.5	1136	4.73		
				6	288	3.1	1409	4.89		
		21.5"x7.3	21.5"x7.3	4	96	2.5	1136	11.83		
				6	144	3.5	1591	11.05		
				8	192	4.3	1955	10.18		
	10			240	5	2273	9.47			
	48	21.5"x7.3	21.5"x7.3	11	264	5.7	2585	9.79	>110	
				4	192	3.5	1588	8.27		
				6	288	5.2	2364	8.21		
				8	384	6.5	2955	7.70		
				10	480	7.6	3447	7.18		
				12	576	8.4	3810	6.61		
		15	720	10.4	4727	6.57				
		20	960	12.6	5727	5.97	<110 after 10 min			
		24.5"x8.1	24.5"x8.1	4	96	2.4	1091	11.36		>70
				6	144	3.4	1545	10.73		
	8			192	4.4	2000	10.42			
	10			240	5.3	2409	10.04			
	12			288	6.1	2773	9.63			
	14			336	6.6	3000	8.93			
	24.5"x8.1	24.5"x8.1	4	192	4	1818	9.47	>100		
			6	288	5.6	2545	8.84			
			6.9	331.2	6.3	2864	8.65			
			8	384	6.8	3091	8.05			
			10	480	7.7	3500	7.29			
			12	576	9	4091	7.10			
			15	720	10	4545	6.31			
			20	960	13.3	6045	6.30		>110	
	24	27"x8	27"x8	4	96	2.8	1273	13.26	>90	
6				144	3.8	1727	11.99			
8				192	4.4	2000	10.42			
10				240	5.2	2364	9.85			
12				288	5.9	2682	9.31			
14				336	6.6	3000	8.93			
16				384	7.2	3273	8.52			
18				432	8	3636	8.42			
48	27"x8	27"x8	2	96	2.7	1227	12.78	>90		
			4	192	4.4	2000	10.42			
			6	288	5.7	2591	9.00			
			8	384	6.7	3045	7.93			
			10	480	7.9	3591	7.48			



Performance Data  
eVP-10 with eVector technology

eVP-10 (300Kv)

ESC	Voltage	Prop	Prop	Current (A)	Power (W)	Thrust (lbs)	Thrust (lbs/g)	Gram/Watt	Operation Temperature (C)
HV-Pro 14s	24	18.5"x6.3	18.5"x6.3	4	96	1.7	773	8.05	>70
				6	144	2.4	1091	7.58	
				8	192	3.3	1500	7.81	
				8.5	204	3.5	1591	7.80	
	48	18.5"x6.3	18.5"x6.3	4.1	196.8	3	1364	6.93	>90
				5.3	254.4	3.8	1727	6.79	
				8.3	398.4	5.5	2500	6.28	
				10.4	499.2	6.3	2864	5.74	
				12.2	585.6	7.3	3318	5.67	
				15	720	8.2	3727	5.18	
	24	21.5"x7.3	21.5"x7.3	4	96	2.2	1000	10.42	>70
				6	144	3	1364	9.47	
				8	192	3.9	1773	9.23	
				10	240	4.7	2136	8.90	
				12	288	5.4	2455	8.52	
				15.2	364.8	6.3	2864	7.85	
	48	21.5"x7.3	21.5"x7.3	4.4	211.2	3.9	1773	8.39	>110
				5.4	259.2	4.5	2045	7.89	
				8	384	6	2721	7.09	
				10.5	504	7	3182	6.31	
				12.2	585.6	7.7	3500	5.98	
				15	720	8.8	4000	5.56	
	24	23.5"x5.5	23.5"x5.5	4	96	1.9	864	9.00	>70
				6	144	2.7	1227	8.52	
				8	192	3.4	1545	8.05	
				10	240	4.1	1864	7.77	
				12	288	4.7	2136	7.42	
				14	336	5.2	2364	7.04	
	48	23.5"x5.5	23.5"x5.5	5.2	249.6	3.9	1773	7.10	>110
				6	288	4.3	1955	6.79	
				8.4	403.2	5.4	2455	6.09	
				10	480	6	2727	5.68	
				12.8	614.4	7.1	3227	5.25	
				15	720	8.2	3727	5.18	
	24	27"x8	27"x8	4	96	2.5	1136	11.83	>115
				6	144	3.4	1545	10.73	
				8	192	4.1	1864	9.71	
				10	240	5	2273	9.47	
				12	288	5.5	2500	8.68	
				15	360	6.5	2955	8.21	
20				480	8	3636	7.58		
25				600	9.2	4182	6.97		
30				720	10.3	4682	6.50		
35	840	11.5	5227	6.22					